

✿ 胶带输送机 Belt Conveyor

胶带输送机已被广泛应用于采矿、冶金、化工、铸造、建材等行业的输送和生产流水线以及水电站建设工地和港口等生产部门，它主要用来输送松散物料或成件物品，根据输送工艺要求，可以单台输送，也可多台胶带输送机组成或与其他输送设备组成水平或倾斜的输送系统，以满足不同布置形式的作业线需要。

Belt Conveyor is widely used in transportation of mining, metallurgy, chemical, foundry, building materials, production lines, construction sites of hydropower stations, ports and other production sectors. It is used to transport loose materials or items. According to transportation process requirements, it can not only be a single conveyor, but also be level or inclined transportation composed of more than one belt conveyor or other transportation equipment, to meet requirements of different layout of the operating line.



规格与性能参数表 Specifications

胶带宽度 Belt width (mm)	输送长度 (米) / 功率 (千瓦) Belt length (m) / Power (kw)			输送速度 Belt speed (m/s)	输送量 Capacity (t/h)
	≤12/4.0	12-20/5.5	20-25/7.5		
400	≤12/4.0	12-20/5.5	20-25/7.5	0.8-2	40-80
500	≤12/4.0	12-20/5.5	20-30/7.5-11.0	0.8-2	78-191
650	≤12/5.5	12-20/7.5	20-30/11	0.8-2	131-323
800	≤10/5.5	10-15/5.5-7.5	15-25/11-15	1.0-2	278-546
1000	≤10/7.5	10-20/11-15	20-25/15-22	1.0-2	435-853
1200	≤10/11.0	12-20/15-22	20-25/22-30	1.0-2	655-1284

数据如有改动恕不另行通知
The data is subject to variation without notice.

✿ 布袋除尘器 Bag Filter

我公司生产的除尘器是借鉴国内外同类产品的先进技术，研制成功的新型高效长布袋除尘器，是在常规短袋冲除尘器的基础上发展起来的一种新型、高效袋式除尘器。具有除尘效率高，占地面积小，运行稳定、性能可靠、维修方便等特点。已被广泛应用于冶金、铸造、建材、矿山、化工等产生烟量、粉尘量大的行业中。

The precipitator that we produced uses domestic and foreign advanced technology for reference successfully developed a new type of high-performance long bag filter is a conventional short pulse bag dust collector developed on the basis of a new, efficient baghouse. Dust with high efficiency, small footprint, stable operation and reliable performance, easy maintenance. It can be widely used in metallurgy, casting, building materials, mining, chemical industry etc, which produce a large quantity of flue gases and dust.



规格与性能参数表 Specifications

型号 Model	处理风量 Air Volume (m³/h)	过滤面积 Filter Area (m²)	风速 Velocity of Wind (m/min)	滤袋规格 Filter-bag Size (mm)	滤袋数量 The number of Filter-bag	脉冲阀 Pulse Valve	风机+卸料+螺旋 Fan+Discharge +Spiral (kw)
DMC25	1200-1920	20	1.0-1.6	Φ130x2000	25	5	1.5+0.75
DMC32	1500-2400	25	1.0-1.6	Φ130x2000	32	5	2.2+0.75
DMC36	1680-2680	28	1.0-1.6	Φ130x2000	36	6	2.2+0.75
DMC49	2340-3740	39	1.0-1.6	Φ130x2000	49	7	3.0+0.75
DMC64	3060-4896	51	1.0-1.6	Φ130x2000	64	8	5.5+0.75
DMC104	6032-9500	104	1.0-1.6	Φ130×2500	104	13	30.0+0.75
DMC112	6720-10752	112	1.0-1.6	Φ130×2500	112	14	45.0+0.75

数据如有改动恕不另行通知
The data is subject to variation without notice.